In the Claims

Below is a list of current claims with status identifiers.

(Currently Amended): A method for automatically processing printer errors occurring during printing of a print job in a virtual printer system wherein a virtual printer is configurable with a plurality of physical print engines, comprising the steps of:

segmenting a print job into a defined job stack for each of the plurality of print engines of the virtual printing system that will print a defined portion of the print job;

detecting occurrence of an error condition during printing of at least a portion of a the associated defined portion of the print job in one of the print engines in the virtual printer system; and re-routing the remainder of the at least a portion of the associated defined portion of the print job not processed by the one print engine to a second print engine in the virtual printer system.

(Currently Amended): The method of Claim \$, wherein the step of detecting comprises the steps of:

reading an error status signal generated by a print engine;

interrupting the at least a portion of the <u>associated defined portion of the</u> print job in which the error status signal was generated; and

releasing the print engine from the virtual printer system in which the error condition occurred.

Currently Amended): The method of Claim, wherein the step of re-routing comprises the steps of:

defining the remainder of the at least a portion of the associated defined portion of the print job; and

attaching a separator page to the remainder of the at least a portion of the <u>associated</u> defined portion of the print job.

AMENDMENT AND RESPONSE S/N 09/484,538 Atty. Dkt. No. TRSY-24,657

567 E7

5

(Currently Amended): The method of Claim 7, wherein the step of defining comprises the step of:

defining the remainder of the at least a portion of the <u>associated defined portion of the</u> print job as the unprinted part of the at least a portion of the <u>associated defined portion of the</u> print job including the page of the at least a portion of the <u>associated defined portion of the</u> print job whereupon the error occurred.

(اع کو

5

5

5

(Currently Amended): The method of Claim 8, wherein the step of attaching comprises the steps of:

creating a separator page associated with the remainder of the at least a portion of the associated defined portion of the print job; and

attaching the separator page to the remainder of the at least a portion of the associated defined portion of the print job.

(Currently Amended): The method of Claim, wherein the step of creating a separator page comprises the step of:

designating an additional page to be inserted in the at least a portion of the associated defined portion of the print job following the last page that resulted in generation of an end-of-page signal.

(Currently Amended): The method of Claim, wherein the step of re-routing comprises the steps of:

reconfiguring the virtual printer system if a second next print engine in the virtual printer system is not available;

printing the re-routed remainder of the at least a portion of the <u>associated defined portion of the</u> print job; and

assembling the pages of the print job printed after re-routing with the pages of the print job printed before re-routing.

AMENDMENT AND RESPONSE

S/N 09/484,538

Atty. Dkt. No. TRSY-24,657

(Currently Amended): An apparatus for automatically processing printer errors occurring during printing of a print job in a virtual printer system wherein a virtual printer is configurable with a plurality of physical print engines, comprising:

a job stacking device for segmenting a print job into a defined job stack for each of the plurality of print engines of the virtual printing system that will print a defined portion of the print job;

a detector for detecting occurrence of an error condition during printing of at least a portion of a the associated defined portion of the print job in one of the print engines in the virtual printer system; and

a router for re-routing the remainder of the at least a portion of the <u>associated defined portion of</u> the print job not processed by the one print engine to a second print engine in the virtual printer system.

(Currently Amended): The apparatus of Claim 1/2, wherein said detector comprises:

a reading device for reading an error status signal generated by a print engine;

an interrupt device for interrupting said at least a portion of said associated defined portion of the print job in which said error status signal was generated; and

a device for releasing said print engine from said virtual printer system in which said error condition occurred.

(Currently Amended): The apparatus of Claim 1/2, wherein said router comprises:

a remainder determination device for defining said remainder of said at least a portion

of said associated defined portion of the print job; and

an attaching device for attaching a separator page to said remainder of said at least a portion of said associated defined portion of the print job.

15. (Currently Amended): The apparatus of Claim 14, wherein said remainder determination device is operable:

to define said remainder of said at least a portion of said <u>associated defined portion of the</u> print job as the unprinted part of said at least a portion of said <u>associated defined portion of the</u> print job

AMENDMENT AND RESPONSE S/N 09/484,538 Atty. Dkt. No. TRSY-24,657

5

10

5

5

including the page of said at least a portion of said associated defined portion of the print job whereupon said error occurred.

から

5

(Currently Amended): The apparatus of Claim 14, wherein said attaching device comprises: a separator device for creating a separator page associated with said remainder of said at least a portion of said associated defined portion of the print job prior to said attaching device attaching said separator page to said remainder of said at least a portion of said associated defined portion of the print job.

(Currently Amended): The apparatus of Claim 14, wherein said attaching device comprises: means for designating an additional page to be inserted in said at least a portion of said associated defined portion of the print job following the last page that resulted in generation of an end-of-page signal.

(Currently Amended): The apparatus of Claim 1/2, wherein said router comprises:

a configuring device for reconfiguring said virtual printer system if a second next print engine in said virtual printer system is not available;

a printer for printing said re-routed remainder of the at least a portion of the <u>associated</u> defined portion of the print job; and

a collator for assembling said pages of said print job printed after after re-routing with said pages of said print job printed before re-routing.

AMENDMENT AND RESPONSE S/N 09/484,538 Atty. Dkt. No. TRSY-24,657